



## BUR Type III

### SECTION 1. IDENTIFICATION

|                                      |  |
|--------------------------------------|--|
| <b>Product Identifier</b>            | BUR Type III   |
| <b>Other Means of Identification</b> | Coating, Oxidised Bitumen  |
| <b>Other Identification</b>          | Asphalt / Bitumen  |
| <b>Recommended Use</b>               | This product is primarily used for roofing applications. However, there are a number of other industrial applications. |
| <b>Restrictions on Use</b>           | None known.  |
| <b>Manufacturer</b>                  | Bitumar Inc., 11155 Rue Sainte Catherine E, Montreal-Est, Quebec, H1B 0A4, 514-645-4561, www.bitumar.com               |
| <b>Emergency Phone No.</b>           | Canutec (Canada), (613) 993-6666; Cel. *666 (canada), 24/7<br>ChemTrec (US), (800) 424-9300, 24/7                      |
| <b>Date of Preparation</b>           | mai 14, 2015   |

### SECTION 2. HAZARDS IDENTIFICATION

#### GHS Classification

Carcinogenicity - Category 2

#### GHS Label Elements



Warning  
Suspected of causing cancer.

#### Other Hazards

Hazard Not Otherwise Classified (HNOC): Contact with hot material can cause thermal burns.

### SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

| Chemical Name     | CAS No.     | %      | Other Identifiers |
|-------------------|-------------|--------|-------------------|
| Asphalt, oxidized | 64742-93-4  | 90-100 |                   |
| Asphalt extender  | 129893-17-0 | 0-10   |                   |
| Hydrogen sulfide  | 7783-06-4   |        |                   |

#### Notes

Sulphur and its derivatives are intrinsic to base asphalt. During storage or transit of hot asphalt, hydrogen sulphide may be generated.

### SECTION 4. FIRST-AID MEASURES

#### First-aid Measures

##### Inhalation

|                      |              |
|----------------------|--------------|
| Product Identifier:  | BUR Type III |
| SDS No.:             | 0055         |
| Date of Preparation: | mai 14, 2015 |

Move to fresh air. Get medical advice/attention if you feel unwell or are concerned.

#### **Skin Contact**

For hot asphalt splash, cool affected body part with water immersion or shower. Do not attempt removal of asphalt but split longitudinally if asphalt covers limb circumferentially to avoid tourniquet effect. No attempt should be made to remove firmly adhering bitumen from the skin.

Once the bitumen has cooled, it will do no further harm. As healing takes place, the bitumen plaque will detach itself, usually after a few days.

#### **Eye Contact**

Immediately rinse the contaminated eye(s) with lukewarm, gently flowing water by allowing the water to flow over the bridge of the nose to the eyes for at least 20 minutes. Seek medical attention.

#### **Ingestion**

DO NOT induce vomiting because of danger of aspirating liquid into lungs. Seek medical attention.

#### **Most Important Symptoms and Effects, Acute and Delayed**

Symptoms may not appear immediately. Fume may cause respiratory irritation; Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness and nose and throat pain. Fume May cause eye irritation.

Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision. Hot liquid product may cause serious thermal burns on direct contact.

#### **Immediate Medical Attention and Special Treatment**

##### **Special Instructions**

No attempt should be made to remove firmly adhering bitumen from the skin. If solvent treatment is used, it should be followed by washing with soap and water, then the application of a proprietary refatting agent or skin cleansing cream. Only medically approved solvents may be used to remove bitumen from burns, as other solvents could cause further skin damage.

## **SECTION 5. FIRE-FIGHTING MEASURES**

#### **Extinguishing Media**

##### **Suitable Extinguishing Media**

Use water to keep non-leaking, fire-exposed containers cool.

SMALL FIRE: use DRY chemicals, foam, water spray or CO<sub>2</sub>.

LARGE FIRE: use water spray, fog or foam.

##### **Unsuitable Extinguishing Media**

None known.

#### **Specific Hazards Arising from the Chemical**

Carbon oxides (CO, CO<sub>2</sub>), nitrogen oxides (NO<sub>x</sub>), sulphur oxides (SO<sub>x</sub>), sulphur compounds (H<sub>2</sub>S), smoke and irritating fumes as products of incomplete combustion.

#### **Special Protective Equipment and Precautions for Fire-fighters**

For small outdoor fires, portable fire extinguishers may be used, and self contained breathing apparatus (SCBA) may not be required. For all indoor fires and any significant outdoor fires, SCBA is required. Respiratory and eye protection are required for fire fighting personnel.

## **SECTION 6. ACCIDENTAL RELEASE MEASURES**

#### **Personal Precautions, Protective Equipment, and Emergency Procedures**

Do not Touch or walk through spilled material. Use the personal protective equipment recommended in Section 8 of this safety data sheet.

#### **Environmental Precautions**

Do not allow into any sewer, on the ground or into any waterway.

#### **Methods and Materials for Containment and Cleaning Up**

Stop or reduce leak if safe to do so. Contain hot liquid by dyking and allow to cool and solidify. Break up and recover, see section 13 for disposal consideration.

---

Product Identifier: BUR Type III

SDS No.: 0055

Page 02 of 06

Date of Preparation: mai 14, 2015

## SECTION 7. HANDLING AND STORAGE

### Precautions for Safe Handling

Asphalt may be transported hot. Avoid skin contact. Avoid eye contact. Avoid inhalation of product vapours or fumes. Ensure all equipment is grounded/bonded. During storage, transit and cooling of asphalt, hydrogen sulphide (H<sub>2</sub>S) may accumulate in enclosed spaces such as tank cars. Open tank car hatches with caution. Maintain same precautions when gauging and sampling. Empty containers may contain product residue. Do not reuse containers without commercial cleaning and/or reconditioning. Personnel who handle this material should practice good personal hygiene during and after handling to help prevent accidental ingestion of this product. Wear proper personal protective equipment.

### Conditions for Safe Storage

To maintain pumping ability, asphalt is kept heated to a suitable temperature; normally well above room temperature but below the flash point. Store in dry, well-ventilated area. Clear roof vents periodically to prevent accumulation of asphalt deposits from vapour accumulation. Store away from incompatible and reactive materials (see section 10). Ensure the storage containers are grounded/bonded.

## SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Control Parameters

| Chemical Name     | ACGIH TLV®  |       | OSHA PEL |         | AIHA WEEL |     |
|-------------------|---|-------|----------|---------|-----------|-----|
|                   | TWA   | STEL  | TWA      | Ceiling | 8-hr TWA  | TWA |
| Hydrogen sulfide  | 1 ppm   | 5 ppm |          |         |           |     |
| Asphalt, oxidized | 0.5 mg/m <sup>3</sup> (as benzene-soluble aerosol) A4 |       |          |         |           |     |
| Asphalt extender  | 0.5 mg/m <sup>3</sup>                                 |       |          |         |           |     |

### Appropriate Engineering Controls

For normal application, special ventilation is not necessary. If user's operations generate vapours or fumes, use ventilation to keep exposure to airborne contaminants below the exposure limit. Make-up air should always be supplied to balance air removed by exhaust ventilation. Ensure that eyewash station and safety shower are close to work-station.

### Individual Protection Measures

#### Eye/Face Protection

As a minimum, safety glasses with side shields should be worn when handling this material.

#### Skin Protection

Wear Protective clothing with full length sleeves and pants should be worn.

#### Respiratory Protection

A minimum of NIOSH-approved air-purifying respirator with an organic vapour cartridge or canister with a dust, fume or mist filter (R, or P series) may be allowable under certain circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by air-purifying respirators is limited. A NIOSH-approved positive-pressure, air-supplied respirator or self-contained breathing apparatus may be required under certain circumstances where airborne concentrations are expected to exceed exposure limits.

## SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

### Basic Physical and Chemical Properties

|                              |                                   |
|------------------------------|-----------------------------------|
| Appearance                   | Brown - black Viscous semi-solid. |
| Odour                        | Asphalt                           |
| Odour Threshold              | Not available                     |
| pH                           | Not available                     |
| Melting Point/Freezing Point | Not available (freezing)          |

Product Identifier: BUR Type III

SDS No.: 0055

Date of Preparation: mai 14, 2015

|   |  |
|---|--|
| <b>Initial Boiling Point/Range</b>                      | > 470 °C (878 °F)  |
| <b>Flash Point</b>                                      | > 288 °C (550 °F) (open cup)   |
| <b>Evaporation Rate</b>                                 | Not available  |
| <b>Flammability (solid, gas)</b>                        | Not applicable   |
| <b>Upper/Lower Flammability or Explosive Limit</b>      | Not available (upper); Not available (lower)   |
| <b>Vapour Pressure</b>                                  | Nil at 37.8°C (100°F)  |
| <b>Vapour Density (air = 1)</b>                         | Not available  |
| <b>Relative Density (water = 1)</b>                     | > 1  |
| <b>Solubility</b>                                       | Insoluble in water; Insoluble in alcohol, acids and alkalis. Soluble in oil turpentine, petroleum, carbon disulphide, chloroform, ether, and acetone |
| <b>Partition Coefficient, n-Octanol/Water (Log Kow)</b> | Not available  |
| <b>Auto-ignition Temperature</b>                        | > 370 °C (698 °F)  |
| <b>Decomposition Temperature</b>                        | Not available  |
| <b>Viscosity</b>  | 150 - 2500 centipoises (dynamic)   |
| <b>Other Information</b>                                |  |
| <b>Physical State</b>                                   | Solid  |

## SECTION 10. STABILITY AND REACTIVITY

### Reactivity

Not reactive under normal conditions of use.

### Chemical Stability

Stable under normal temperature conditions and recommended use.

### Possibility of Hazardous Reactions

None known.

### Conditions to Avoid

Open flames, sparks, static discharge, heat and other ignition sources. Incompatible materials.

### Incompatible Materials

Oxidizing agents (e.g. peroxides), fluorine.

### Hazardous Decomposition Products

Carbon Oxides (COx), sulfur Oxides (SOx), nitrogen oxides (NOx), hydrogen sulfide, hydrocarbons.

## SECTION 11. TOXICOLOGICAL INFORMATION

### Likely Routes of Exposure

Eye contact; skin contact; inhalation; ingestion.

### Acute Toxicity

| Chemical Name    | LC50                            | LD50 (oral)   | LD50 (dermal) |
|------------------|---------------------------------|---------------|---------------|
| Hydrogen sulfide | 444 ppm (rat) (4-hour exposure) |               |               |
| Asphalt extender | Not available                   | Not available | Not available |

### Skin Corrosion/Irritation

Prolonged or repeated contact with skin may cause dermatitis or warty skin growths (keratosis). Contact with hot material can cause thermal burns.

### Serious Eye Damage/Irritation

Product Identifier: BUR Type III  
 SDS No.: 0055  
 Date of Preparation: mai 14, 2015

Vapours or fumes from the hot asphalt can cause irritation of the surface of the eyes as well as limbal pigmentation of the cornea. Contact with hot material can cause thermal burns.

#### **STOT (Specific Target Organ Toxicity) - Single Exposure**

##### **Inhalation**

No information was located.

##### **Skin Absorption**

No information was located.

##### **Ingestion**

No information was located.

#### **Aspiration Hazard**

May cause lung damage if aspirated based on physical properties (e.g. kinematic viscosity) and chemical family (hydrocarbon).

#### **STOT (Specific Target Organ Toxicity) - Repeated Exposure**

No information was located.

#### **Respiratory and/or Skin Sensitization**

This product is not expected to be a skin or a respiratory tract sensitizer, based on the available data and the known hazards of the components.

#### **Carcinogenicity**

| <b>Chemical Name</b> | <b>IARC</b> | <b>ACGIH®</b>  | <b>NTP</b> | <b>OSHA</b> |
|----------------------|-------------|----------------|------------|-------------|
| Asphalt, oxidized    | Group 2A    | A4             | Not Listed | Carcinogen  |
| Asphalt extender     | Not Listed  | Not designated | Not Listed | Not Listed  |

Group 2A – Probably carcinogenic to humans. Group 2B – Possibly carcinogenic to humans.

#### **Other Information**

Contains:

HYDROGEN SULFIDE : Chronic health effects due to repeated exposures to low levels of H<sub>2</sub>S have not been established. High level (700 ppm) acute exposure can result in sudden death. High concentrations will lead to cardiopulmonary arrest due to nervous system toxicity and pulmonary edema. Lower levels (150 ppm) may overwhelm sense of smell, eliminating warning of exposure. Symptoms of over exposure to H<sub>2</sub>S include headache, fatigue, insomnia, irritability, and gastrointestinal problems. Repeated exposures to approximately 25 ppm will irritate mucosa membranes and the respiratory system and have been implicated in some eye damage.

## **SECTION 12. ECOLOGICAL INFORMATION**

#### **Toxicity**

Not Available.

#### **Persistence and Degradability**

Not Available.

#### **Bioaccumulative Potential**

Not Available.

#### **Mobility in Soil**

Not Available.

#### **Other Adverse Effects**

Not Available.

## **SECTION 13. DISPOSAL CONSIDERATIONS**

#### **Disposal Methods**

Dispose of waste at an appropriate treatment & disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

Product Identifier: BUR Type III  
SDS No.: 0055  
Date of Preparation: mai 14, 2015

## SECTION 14. TRANSPORT INFORMATION

| Regulation | UN No. | Proper Shipping Name                            | Transport Hazard Class(es) | Packing Group |
|------------|--------|---|----------------------------|---------------|
| US DOT     | UN3257 | Elevated temperature liquid (Bitumen (Asphalt)) | 9                          | III           |

**Special Precautions for User** Not applicable

**Transport in Bulk According to Annex II of MARPOL 73/78 and the IBC Code**

Not applicable

**Emergency Response Guide No.** 130

## SECTION 15. REGULATORY INFORMATION

**Safety, Health and Environmental Regulations**

**Canada**

**Domestic Substances List (DSL) / Non-Domestic Substances List (NDSL)**

All ingredients are listed on the DSL or are not required to be listed.

**USA**

**Toxic Substances Control Act (TSCA) Section 8(b)**

All ingredients are on the TSCA Inventory or are exempt from TSCA Inventory requirements under 40 CFR 720.

## SECTION 16. OTHER INFORMATION

**NFPA Rating** Health - 1 Flammability - 1 Instability - 0

**SDS Prepared By** R&D and Technical group

**Phone No.** 514-645-4561

**Date of Preparation** mai 14, 2015

**Disclaimer** Bitumar Inc. customarily reviews and updates SDS within 90 days of new data availability in accordance with Canadian Hazardous Products Act. If you would like to verify if the MSDS you have is the most current, or you require any further information, please contact:  
[www.bitumar.com](http://www.bitumar.com)  
Ontario/Central/Quebec & Eastern Canada, telephone: 514-645-4561; fax: 514-645-6978.  
For the USA: 410-354-9550. Fax: 410-354-9552.  
For other Product Safety Information: (514) 645-4561

To the best of our knowledge, the information contained herein is accurate. However, neither BITUMAR Inc. nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist

---

Product Identifier: BUR Type III

SDS No.: 0055

Page 06 of 06

Date of Preparation: mai 14, 2015