Material Safety Data Sheet





1. Product and company identification

Product name : CR60

Material uses : Concrete and masonry structures waterproofing coating.

Supplier/Manufacturer : CONDOR CHIMIQUES

2645-B, Boul. Terra-Jet St-Cyrille-de-Wendover, Qc J1Z 1B3, Canada

Tél: (819) 474-6661 Fax: (819) 474-6681 Courriel: info@condor.pro

Validation date : 2016-01-03

Responsible name : SIMDUT Group.

In case of emergency : (819) 474-6661 ou CANUTEC (613) 996-6666

2. Hazards identification

Physical state : Liquid.

Odor : Solvent.

Emergency overview : WARNING!

COMBUSTIBLE LIQUID AND VAPOR. CAUSES EYE AND SKIN IRRITATION. CONTAINS

MATERIAL THAT CAN CAUSE TARGET ORGAN DAMAGE.

Keep away from heat, sparks and flame. Avoid exposure - obtain special instructions before use. Do not breathe vapor or mist. Avoid contact with eyes, skin and clothing. Contains material that can cause target organ damage. Use only with adequate ventilation. Keep container tightly closed and sealed until ready for use. Wash thoroughly after handling.

Potential acute health effects

Inhalation:Slightly irritating to the respiratory system.Ingestion:No known significant effects or critical hazards.

Skin : Irritating to skin.

Eyes : Irritating to eyes.

Potential chronic health effects

Chronic effects : Contains material that can cause target organ damage.

Carcinogenicity: No known significant effects or critical hazards.Mutagenicity: No known significant effects or critical hazards.Teratogenicity: No known significant effects or critical hazards.Developmental effects: No known significant effects or critical hazards.Fertility effects: No known significant effects or critical hazards.

Target organs : Contains material which causes damage to the following organs: kidneys, upper

respiratory tract, skin, central nervous system (CNS), eye, lens or cornea.

2. Hazards identification

Over-exposure signs/symptoms

Inhalation : Adverse symptoms may include the following:

respiratory tract irritation

coughing

Ingestion : No specific data.

Skin : Adverse symptoms may include the following:

irritation redness

Eyes : Adverse symptoms may include the following:

pain or irritation watering redness

Medical conditions

aggravated by overexposure

Pre-existing disorders involving any target organs mentioned in this MSDS as being at

risk may be aggravated by over-exposure to this product.

See toxicological information (section 11)

3. Composition/information on ingredients

Name	CAS Number	%
Stoddart solvent	8052-41-3	15 - 40

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section

4. First aid measures

Eye contact : Check for and remove any contact lenses. In case of contact with eyes, rinse immediately with plenty

of water. Get medical attention.

Skin contact : Wash with soap and water. Get medical attention if symptoms occur.

Inhalation : If inhaled, remove to fresh air. If not breathing, give artificial respiration. Get medical attention if

symptoms occur.

Ingestion : Do not induce vomiting. Never give anything by mouth to an unconscious person. Get medical

attention.

Protection of first-aiders : No action shall be taken involving any personal risk or without suitable training. If it is suspected that

fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

Notes to physician : No specific treatment. Treat symptomatically. Contact poison treatment specialist immediately if large

quantities have been ingested or inhaled.

5. Fire-fighting measures

Flammability of the product : Combustible

Extinguishing media

Suitable : Use dry chemical, CO2, water spray (fog) or foam.

Not suitable : Do not use water jet.

Special exposure hazards : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No

action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

5. Fire-fighting measures

Hazardous thermal decomposition products

Decomposition products may include the following materials:

carbon dioxide carbon monoxide sulfur oxides

Special protective equipment for fire-fighters

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus

(SCBA) with a full face-piece operated in positive pressure mode.

6. Accidental release measures

Personal precautions

No action shall be taken involving any personal risk or without suitable training.

Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment (see section 8).

Environmental precautions

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods for cleaning up

Small spill

Absorb spill with inert material (e.g. dry sand or earth) and place in a chemical waste container.

Large spill

Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see section 1 for emergency contact information and section 13 for waste disposal.

7. Handling and storage

Handling

Put on appropriate personal protective equipment (see section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not re-use container.

Storage

Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10) and food and drink. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

8. Exposure controls/personal protection

Product name

Exposure limits

Stoddart solvent

ACGIH TLV (United States, 1/2006). TWA: 525 mg/m³ 8 hour(s).

Consult local authorities for acceptable exposure limits.

8. Exposure controls/personal protection

Recommended monitoring procedures If this product contains ingredients with exposure limits, personal, workplace atmosphere

or biological monitoring may be required to determine the effectiveness of the ventilation or other

control measures and/or the necessity to use respiratory protective equipment.

Engineering measures Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other

> engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below

any lower explosive limits.

Hygiene measures Wash hands, forearms and face thoroughly after handling chemical products, before

eating, smoking and using the lavatory and at the end of the working period. Appropriate

techniques should be used to remove potentially contaminated clothing. Wash

contaminated clothing before reusing. Ensure that eyewash stations and safety showers

are close to the workstation location.

Personal protection

Safety glasses. **Eyes**

Skin Wear appropriate personal protective suit.

Respirator selection must be based on known or anticipated exposure levels, the Respiratory

hazards of the product and the safe working limits of the selected respirator.

Hands Natural rubber (latex).

Personal protective

equipment (Pictograms)



HMIS Code/Personal protective equipment

Environmental exposure

controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

9. Physical and chemical properties

Physical state Liquid.

Flash point Closed cup: 43°C (109.4°F) [Pensky-Martens.]

В

Flammable limits Lower: 1% Upper: 6 %

Self-burning temperature 245°C (solvent)

Color Black. Odor Solvent. Relative density 0.965 g/ml

Vapor pressure (38°C) 0.93 kPa (7 mm Hg)

Vapor density 3.9 [Air = 1]Volatility 30 to 35% (v/v)

0.10 à 0.15 (Butyl acetate. = 1) **Evaporation rate**

Boiling point 90-150°C

Viscosity 48000-60000 Cps VOC <350 g/L Maximum Solubility Insoluble in water.

10. Stability and reactivity

Stability : The product is stable.

Hazardous polymerization : Under normal conditions of storage and use, hazardous polymerization will not occur.

Conditions to avoid : Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill,

grind or expose containers to heat or sources of ignition. Do not allow vapor to accumulate in low or

LD Oral

confined areas. Avoid exposure - obtain special instructions before use.

Materials to avoid : Reactive or incompatible with the following materials:

oxidizing materials

Hazardous decomposition

products

Under normal conditions of storage and use, hazardous decomposition products should not be

produced.

Conditions of reactivity : Flammable in the presence of the following materials or conditions: open flames, sparks and static

discharge.

Slightly flammable in the presence of the following materials or conditions: heat.

>5 g/kg

11. Toxicological information

Acute toxicity

Product/ingredient nameSpeciesDoseResultExposureStoddart solventRabbit>3 g/kgLD Dermal-

Rat

 Inhalation
 :
 Slightly irritating to the respiratory system.

 Ingestion
 :
 No known significant effects or critical hazards.

Skin : Irritating to skin.

Eyes : Irritating to eyes.

Carcinogenicity

Classification

Product/ingredient name ACGIH CIRC EPA NIOSH NTP OSHA

12. Ecological information

Environmental effects : No known significant effects or critical hazards

13. Disposal considerations

Waste disposal : The generation of waste should be avoided or minimized wherever possible. Empty containers or liners

may retain some product residues. This material and its container must be disposed of in a safe way. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any byproducts should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees.

14. Transport information

AERG : 130

Regulatory information	UN number	Proper shipping name	Classes	PG*	Label	Additional information
TDG Classification	UN 1999	Tars liquid including road asphalt and tar cut backs	3	III		-
IMDG Class	UN 1999	Tars liquid including road asphalt and tar cut backs	3	III		-
IATA-DGR Class	UN 1999	Tars liquid including road asphalt and tar cut backs	3	III	&	-

15. Regulatory information

Canada

WHMIS (Canada) : Class B-3: Combustible liquid with a flash point between 37.8°C

(100°F) and 93.3°C (200°F).

Class D-2B: Material causing other toxic effects (Toxic).

Canadian lists : CEPA Toxic substances: None of the components are listed.

Canadian ARET: None of the components are listed.

Canadian NPRI: The following components are listed: Stoddart solvent Alberta Designated Substances: None of the components are listed. Ontario Designated Substances: None of the components are listed. Quebec Designated Substances: None of the components are listed.

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

GHS (United Nation, Purple Book)

Classification of the : FLAMMABLE LIQUIDS - Category 3

substance or mixture SKIN CORROSION/IRRITATION - Category 2

SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2B

SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) Respiratory tract

irritation - Category 3

SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) central nervous

system (CNS), kidneys and respiratory tract - Category 2

GHS label elements

Signal word : Danger

Hazard statements : Flammable liquid and vapor.

Causes skin irritation. Causes eye irritation.

May cause respiratory irritation.

May cause damage to organs through prolonged or repeated exposure if inhaled.

(respiratory tract)

May cause damage to organs through prolonged or repeated exposure if swallowed.

(central nervous system (CNS), kidneys)



15. Regulatory information

Precautionary statements

Prevention : Read label before use. Wear protective gloves. Wear eye/face protection. Keep away from ignition

sources such as heat/sparks/open flame. - No smoking. Keep container tightly closed. KEEP OUT OF REACH OF CHILDREN. Do not breathe vapor. Wash thoroughly after handling. If medical advice is

needed: Have product container or label at hand.

Response : IF ON SKIN (or hair): Take off contaminated clothing and wash before re-use. Rinse skin with water

and/or take a shower. Wash with plenty of soap and water. If skin irritation occurs, seek medical advice/attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists, get medical advice/attention. Wash

hands after handling. Get medical attention/advice if you feel unwell.

Storage : Store locked up. Store in cool/well-ventilated place.

Disposal ; Dispose of contents and container in accordance with all local, regional, national and international

regulations.

Symbole



Not available





Other hazards which do not result in classification

International regulations

International lists : This product, (and its ingredients) is (are) listed on national inventories, or is (are) exempted from

being listed, in Australia (AICS), in Europe (EINECS/ELINCS), in Korea (TCCL), in Japan (METI), in

the Philippines (RA6969).

16. Other information

Label requirements : COMBUSTIBLE LIQUID AND VAPOR. CAUSES EYE AND SKIN IRRITATION. MAY CAUSE

RESPIRATORY TRACT IRRITATION. CONTAINS MATERIAL THAT CAN CAUSE TARGET ORGAN

DAMAGE.

Hazardous Material Information System

(U.S.A.)

Health	*	1	
Fire hazard		2	
Physical Hazard			
Protection individuelle			

HAZARD RATINGS

4- Extreme

3- Serious 2- Moderate

1- Slight

0- Minimal

See section 8 for more detailed information on personal protection

The customer is responsible for determining the PPE code for this material.

National Fire Protection Association (U.S.A.)

Health



Flammability Instability

Special

16. Other information

References

ANSI Z400.1, MSDS Standard, 2004. - Manufacturer's Material Safety Data Sheet. - Canada Gazette Part II, Vol. 122, No. 2. Registration SOR/88-64, 31 December 1987. Hazardous Products Act "Ingredient Disclosure List" - Canadian Transport of Dangerous

Goods, Regulations and Schedules, Clear Language version 2005.

Date of issue January 03, 2016.

Version

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.