

# ROOFMAX

## INSULTAC MP

### MANUAL POWERED APPLICATORS

#### DESCRIPTION & USE

Insultac Manual Powered Applicators are specially designed to be used with the Insultac family of adhesives and sealants. They are powered by manually squeezing the trigger on the handle of the applicator which drives the piston rods. These applicators are recommended for smaller roofs or congested areas.

The MP1 Applicator is a premium quality hand tool that produces approximately 1,100 pounds of thrust, while the MP2 Applicator produces approximately 900 pounds of thrust.

#### FEATURES & BENEFITS

**Manual powered** - works like a caulking gun.

**Quick and easy to use** - saves time and labour.

**Centre drive design** - ensures an equal mix every time.

#### PACKAGING

MP1 Applicator is orange and sold per unit.

MP2 Applicator is black and sold per unit.

#### USER INSTRUCTIONS

1. Install mixing nozzle on cartridge. Prepare cartridge for loading according to adhesive manufacturer recommendations.
2. Ensure the piston rods are fully retracted. Place the rear of the cartridge over the pistons and then lower the front of the cartridge into the carriage and line up mixing nozzle opening.
3. Once the cartridge is loaded into the applicator draw the pistons up to the cartridge seals (plungers) by pushing on the piston rack. Squeeze the trigger located on the handle to begin dispensing adhesive.
4. To stop, release the trigger and press the thumb activated release located on the back side of the handle to relieve pressure.
5. To retract the pistons, simply press the thumb activated release button and pull back upon the piston rack until it is fully retracted.



#### Maintenance Instructions

- Keep the applicator clean. Remove adhesive and/or contamination from pistons and drive rods before it hardens. Do not allow cured adhesive to build-up on pistons.
- Check the pistons and all fasteners routinely for tightness and proper function.

#### SAFETY RECOMMENDATIONS

Protective equipment such as safety glasses and protective gloves must be worn when operating or servicing this tool. The applicator should never be pointed at, or near, people. The applicator should never be operated when the outlet tip of the adhesive cartridge is blocked or restricted by cured adhesive, any object, or some part of the body.

Prior to working with this or any product consult product label and Safety Data Sheet (SDS) for necessary health and safety precautions.

lexcor.net

#### COMMERCIAL BUILDING PRODUCTS

Ontario & Western Canada  
1.800.268.2889



Quebec & Atlantic Canada  
1.800.363.2307