

LEXCAN

HI-PRO PVC

Membrane Cleaner

DESCRIPTION & USE

Lexcan Hi-Pro PVC Membrane Cleaner is a solvent used to clean new and in-service PVC membrane that has been exposed to the weather prior to the welding process. This cleaner helps to loosen and remove dirt and other contaminants from the surface of the PVC membranes and leaves a suitable surface for welding.

FEATURES & BENEFITS

- Cleans new and in-service PVC membranes.
- Helps to loosen and remove dirt and other contaminants from membrane surfaces.
- Gentler to membranes than other available solvents.

TECHNICAL DATA

Physical Properties	
Colour:	Clear
Flash Point:	-20°C (-4°F)
Solubility in Water:	Complete
Boiling Point:	56.1°C (133°F)
Packaging:	18.9L (5-gallon) closed top pail
VOC:	VOC Exempt

Coverage Rates

Depends on the age of the membrane and the amount of dirt and debris on the surface. Assume 400 square feet (37.2 square meters) (one surface) per 3.8 litres (1 gallon).

CAUTIONS & LIMITATIONS

- In case of fire handle as a solvent or gasoline fire. Use dry chemical, carbon dioxide or foam fire extinguishers. Water fog or spray may be used to smother the fire and cool containers. Do not use a solid stream of water to fight fire because it can scatter and spread the fire.
- See SDS for complete safety information before using product.

APPLICATION INSTRUCTIONS

1. Use solvent resistant gloves when handling product.
2. Excessively dirty membrane will require pre-cleaning with a household cleaner prior to using Hi-Pro PVC Membrane Cleaner.
3. Clean all mating surfaces by saturating clean Lexcan Splice Cleaning Cloths with Hi-Pro PVC Membrane Cleaner.
4. Wipe the area to be cleaned until it is a consistent colour with no streaking.
5. Change cleaning cloths frequently so as not to redeposit dirt.
6. Allow surfaces to dry before hot air welding or application of adhesive.