

CONTRACTOR'S SHEATHING TAPE



DESCRIPTION

This tape is made of a UV resistant polypropylene film and coated with high shear, high tack solvent based acrylic adhesive

MAIN FEATURES

- High shear adhesive provides aggressive contact.
- Strong and durable holding power.
- Water and moisture resistant.
- Excellent resistance to UV and weathering.
- Prevents air infiltration.
- CCMC approved, see Report #11955.

APPLICATIONS

- Sealing of joints and seams of insulation materials.
- Tape has to be pressed firmly on surface.
- Should be applied on clean, dry surfaces.

TECHNICAL DATA

Colour	Red with Black Print
Backing	UV Resistant Polypropylene Film
Adhesive.....	Solvent Based Acrylic
Thickness.....	3.0 mil
Adhesion to steel.....	40 oz/in
Tensile strength	30 lb./in
Elongation	120%
Application Temperature.....	-10°C (14°F) • 50°C (122°F)
Cold Temperature Resistance.....	-40°C • -40°F
VOC (Volatile Organic Compound) content	Estimated 0,1%
Moisture Vapor Transmission Rate.....	3.9x10 ⁻⁹ g/Pa s m ²
Water Penetration Rate.....	0.009 g/100 in ²

STOCK SIZE

60mm x 66m -- 20 rolls/case

Please note:

Specifications quoted are averages only and may vary within industry tolerances. The final user must assure product suitability for the application and assumes all risks and liabilities.

STRONG HOLDING POWER

HIGH TACK ADHESIVE