





Protective Safety Gloves Glasses

WHMIS Pictograms

Not Controlled

DOT Pictograms

Not Regulated

SECTION 1 - PRODUCT AND COMPANY IDENTIFICATION

Product Name: Foamular® Extruded Polystyrene Insulation - Zero Ozone

Depletion Formula

MSDS Manufacturer

Number:

10010796-NAM

Synonyms:

Foamular \$ 150, Foamular \$ 250, Foamular \$ 350, Foamular \$Foamular® CodeBord®, Foamular® Cel-Lok®, Foamular® CW15, Foamular® CW25, Foamular® LT30, Foamular® LT40, Foamular® 404RB, Foamular® 604RB, Foamular® AgTek, Foamular® PROPINK®, Foamular® DURAPINK®, Foamular® PINKCORE®, Foamular® PINKCORE® TT, Foamular® Half-Inch, Foamular® INSULPINK®, Foamular® THERMAPINK®, Foamular® DURAPINK® FA, Foamular® DURAPINK® Plus, Foamular® INSULPINK® - Z, Foamular® THERMAPINK® 18, Foamular® THERMAPINK® 25, Foamular® THERMAPINK® 40, Foamular® THERMAPINK® 60, Foamular® Extruded Polystyrene, Foamular® Insulating Sheathing, Foamular®

INSUL-DRAIN®

Manufacturer Name: Owens Corning Foam Insulation, LLC

Address: One Owens Corning Parkway Toledo, OH 43659

1-800-GET-PINK or 1-800-438-7465 Customer Service Phone

Number:

Health Issues Information: 1-419-248-8234 (8am-5pm ET)

Technical Product 1-800-GET-PINK or 1-800-438-7465

Information:

Emergency Phone Number: 1-419-248-5330 (after 5pm ET and weekends)

CHEMTREC: 800-424-9300 (24 hours everyday)

Canutec: (613) 996-6666 (Canada 24 hours everyday)

Website: www.owenscorning.com March 06, 2009 MSDS Creation Date: MSDS Revision Date: September 15, 2009

NFPA



Chronic Health Effects

SECTION 2 - COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS#	Ingredient Percent
Blended Blowing Agent	Proprietary	1 - 10 by weight
Polystyrene	9003-53-6	80 - 95 by weight
Hexabromocyclododecane	3194-55-6	0.5 - 1.5 by weight
Non-Hazardous Statement:.	The remaining components of this product are non-hazardous or are in a small enough quantity as to not meet regulatory thresholds for disclosure. These components contain no substances or impurities which would influence the classification of this product.	

SECTION 3 - HAZARDS IDENTIFICATION

Applies to Product:

Emergency Overview: Dense Black Smoke will be produced during a fire.

Grinding, sawing or fabrication activities can produce dust particles which under

certain conditions may ignite or form explosive dust atmospheres. Flammable vapors may be produced in unventilated storage.

Route of Exposure: Eye contact

Inhalation.

Potential Health Effects:

Eye: Dust may cause slight irritation. Skin: No effects expected.

Inhalation: Dust may cause irritation of respiratory tract.

Ingestion of this product is unlikely. Ingestion:

Chronic Health Effects: There is no known chronic health effect connected with long-term use or contact

with this product.

This material is not considered a carcinogen. Carcinogenicity:

Potential Environmental Effects: There is no known ecological information for this material.

Aggravation of Pre-Existing Chronic respiratory or skin conditions may temporarily worsen from exposure to

Conditions: this product.

OSHA Regulatory Status: This product is considered hazardous by the OSHA Hazard Communication

Standard (29 CFR 1910.1200).

Appearance and Odor: Pink, white, gray, black or green closed-cell foam board with no odor.

SECTION 4 - FIRST AID MEASURES

Eye Contact: Immediately flush eyes with plenty of water for at least 15 to 20 minutes. Ensure

adequate flushing of the eyes by separating the eyelids with fingers.

Do not rub or scratch eyes.

If eye irritation persists, consult a specialist. $Immediately \ wash \ skin \ with \ soap \ and \ plenty \ of \ water.$

Skin Contact: Get medical attention if irritation develops or persists.

Inhalation: Move to fresh air.

If symptoms persist, call a physician.

Accidental ingestion of this material is unlikely. Indestion:

If this does occur, watch person for several days to make sure intestinal blockage

does not occur.

If symptoms persist, call a physician.

SECTION 5 - FIRE FIGHTING MEASURES

Flammable Properties: Combustible Flash Point: >615 °F (324 °C) Flash Point Method: **ASTM D 1929** Auto Ignition Temperature: Not applicable. Lower Flammable/Explosive Limit: Not applicable. Upper Flammable/Explosive Limit: Not applicable. Extinguishing Media: dry chemical

foam

carbon dioxide (CO2)

water fog

Unsuitable Media:

Wear self-contained breathing apparatus (SCBA) and full fire fighting protective Protective Equipment:

Unusual Fire Hazards: Grinding, sawing or fabrication activities can produce dust particles which under

certain conditions may ignite or form explosive dust atmospheres.

Hazardous Combustion Carbon monoxide. Byproducts: Carbon dioxide.

styrene.

Small quantities of hydrogen fluoride, hydrogen chloride, fluorine and chlorine

could be released

Other undetermined compounds could be released in small quantities.

Universal Fire And Explosion

Hazards:

NFPA Ratings:

NFPA Health: 0 NFPA Flammability: 1 0 NFPA Reactivity:

NFPA Other:

SECTION 6 - ACCIDENTAL RELEASE MEASURES

Personnel Precautions: Avoid contact with skin and eyes. This material will settle out of the air. Methods for containment:

Prevent from spreading by covering, diking or other means.

Methods for cleanup: Use an industrial vacuum cleaner with a high efficiency filter to clean up dust.

Avoid dry sweeping.

Pick up and transfer to properly labeled containers. After cleaning, flush away traces with water.

Other Precautions: Does not apply.

SECTION 7 - HANDLING and STORAGE

Handling: Extinguish all smoking or other ignition sources.

Avoid dust formation. Do not breathe dust.

Wear personal protective equipment.

Storage: To prevent build-up of flammable vapors, do not store large quantities of this

product in unventilated spaces.

Special Handling Procedures: Flammable vapors may be generated during unventilated storage of large amounts

of this product. (ex. storage trailers)

SECTION 8 - EXPOSURE CONTROLS, PERSONAL PROTECTION - EXPOSURE GUIDELINES

Engineering Controls: Provide local exhaust and/or general ventilation.

Eye/Face Protection: Safety glasses with side-shields.

Skin Protection Description: Protective gloves.

Long sleeved shirt and long pants.

Respiratory Protection: When workers are facing airborne particulate/dust concentrations above the

exposure limit they must use appropriate certified respirators.

General Hygiene Considerations: Wash hands before breaks and immediately after handling the product.

Remove and wash contaminated clothing before re-use.

EXPOSURE GUIDELINES

Guideline OSHA Guideline ACGIH Ontario Canada

5 mg/m3, 3 mg/m3, 3 mg/m3, Polystyrene Respirable, 10 respirable, 10 respirable, 10 mg/m3, Total mg/m3, inhalable mg/m3, inhalable

Particulates Not particles (NOS) Particulates (Insoluble) Not Otherwise Classified (PNOC) Otherwise Classified

SECTION 9 - PHYSICAL and CHEMICAL PROPERTIES

Physical State: Solid, Board, Pellets

Physical State Appearance: Foam.

Pink, white, gray, black or green

Odor: No detectable odor.

Boiling Point: Decomposes over600 °F (316 °C) Melting Point: Softens @ 220 °F (104 °C) 0.021-0.064 (Ref: water = 1). Specific Gravity:

Solubility: Insoluble in water.

Vapor Density: No Data Vapor Pressure: No Data Evaporation Rate: No Data pH: No Data

Flash Point: >615 °F (324 °C) Flash Point Method: **ASTM D 1929** Not applicable. Auto Ignition Temperature:

SECTION 10 - STABILITY and REACTIVITY

Chemical Stability: Stable under normal conditions.

Hazardous Polymerization: Hazardous polymerization does not occur.

Conditions to Avoid: Dust dispersion in air. Incompatible Materials: Hydrocarbons

Amines

Special Decomposition Products: See Section 5 of MSDS for hazardous decomposition products during a fire.

SECTION 11 - TOXICOLOGICAL INFORMATION

Applies to Product:

Dusts may cause mechanical irritation to eyes and skin. Ingestion may cause Acute Toxicity: transient irritation of throat, stomach and gastrointestinal tract. Inhalation may

cause coughing, nose and throat irritation, and sneezing. High exposures may

cause difficulty breathing, congestion, and chest tightness.

Carcinogens:

ACGIH NIOSH OSHA IARC NTP MEXICO

Group 3 - Not Polystyrene No Data No Data No Data No Data No Data Classifiable as to

> its Carcinogenicity to Humans.

No Data No Data No Data No Data No Data No Data Hexabromocyclododecane

Applies to Product:

No information available. Sensitization: No information available. Mutagenicity: Reproductive Toxicity: No information available. Teratogenicity: No information available. Neurological Effects: No information available. <u>Hexabromocyclododecane</u>:

Skin - Rabbit LD50: >8 gm/kg [Details of toxic effects not reported other than

lethal dose value.](RTECS)

Ingestion: Inhalation. - Rat LD50: >10 gm/kg [Details of toxic effects not reported other than

lethal dose value.](RTECS)

SECTION 12 - ECOLOGICAL INFORMATION

Applies to Product:

Ecotoxicity: This material is not expected to cause harm to animals, plants or fish.

Environmental Fate: No data available for this product.

Bioaccumulation: Not available.
Biodegradation: Not available.
Mobility In Environmental Media: Not available.

SECTION 13 - DISPOSAL CONSIDERATIONS

Applies to Product:

Waste Disposal: Dispose of in accordance with Local, State, Federal and Provincial regulations.

Contaminated Packaging: Empty containers should be taken for local recycling, recovery or waste disposal.

RCRA Number: No EPA Waste Numbers are applicable for this product's components.

RCRA Characteristics: This material is not expected to be a characteristic hazardous waste under RCRA.

SECTION 14 - TRANSPORT INFORMATION

DOT Shipping Name: Not Regulated. Not Regulated. IATA Shipping Name: Canadian Shipping Name: Not Regulated. IMDG Shipping Name: Not Regulated. ADR Shipping Name: Not Regulated. RID Shipping Name: Not Regulated. ICAO Shipping Name: Not Regulated. MEX Shipping Name : Not Regulated.

SECTION 15 - REGULATORY INFORMATION

Inventory Status

Japan ENCSELINCSEINECS NumberPICCSSouth KoreaPolystyrene(6)-120500-008-9KECLKE-13257Hexabromocyclododecane221-695-9ListedKE-18398

Austrailia AICS Canada DSL EINECS Inventory TSCA Inventory
Status

Polystyrene Listed Listed No Listed

Hexabromocyclododecane Listed Listed Yes Listed

Applies to Product:

Canada Reg. Status: This product has been classified in accordance with the hazard criteria of the

Controlled Products Regulations and the MSDS contains all of the information $% \left(1\right) =\left(1\right) \left(1$

required by the Controlled Products Regulations.

Canada WHMIS: Not controlled.

CA PROP 65: The following statement(s) are provided under the California Safe Drinking Water

and Toxic Enforcement Act of 1986 (Proposition 65):

This product does not contain any Proposition 65 chemicals.

Section 311/312 Hazard

Categories: A cute Health Hazard: No Chronic Health Hazard: No

Chronic Health Hazard: No Risk of ignition: No Sudden Release of Pressure Hazard: No Reactive Hazard: No

Clean Air Act: This product does not contain any Hazardous Air Pollutants (HAPs).

State Right To Know

RIMNILPAMAPolystyreneNo DataNo DataNo DataNo DataNo DataHexabromocyclododecaneNo DataNo DataNo DataNo Data

NJ

Polystyrene No Data Hexabromocyclododecane No Data

Foamular® Extruded Polystyrene Insulation - Zero Ozone Depletion Formula Revison:09/15/2009, Version:0.0000

SECTION 16 - ADDITIONAL INFORMATION

HMIS Health Hazard: 0
HMIS Fire Hazard: 1
HMIS Reactivity: 0
HMIS Personal Protection: X

MSDS Creation Date: March 06, 2009
MSDS Revision Date: September 15, 2009
MSDS Revision Notes: Updated Product Synonyms

Disclaimer: Reasonable care has been taken in the preparation of this information, but the

manufacturer makes no warranty of merchantability or any other warranty, expressed or implied, with respect to this information. The manufacturer makes no representations and assumes no liability for any direct, incidental or consequential

damages resulting from its use.

 $Copyright @ \ 1996-2008 \ \underline{Actio\ Software\ Corporation}. \ All\ Rights\ Reserved.$

Foamular® Extruded Polystyrene Insulation - Zero Ozone Depletion Formula Revison:09/15/2009, Version:0.0000