

Product Name:	Basketweave 24x30
Product Type:	Classic Series Slab

Product Specifications	Length x Width x Height	Length x Width x Height	Length x Width x Height
Dimensions Metric (mm):	600 x 750 x 40		
Dimensions Imperial (inches):	23.62 x 29.52 x 1.57		
Individual Weight Kg:	43.72		
Individual Weight lbs:	96.40		
Pieces per Bundle	25		
Units per Layer			
Bundle Weight Kg	1093.0		
Bundle Weight Lbs	2410.0		
Product Texture:			

### Product Uses:

Residential	Commerical				Other		
		Pedestrian	Pedestrian	Vehicular		Slab on	
Pedestrian	Vehicular	only	& Vehicular	Traffic	Accessibility	Pedestal Set	Permeable
$\boxtimes$		X				X	

### **Physical Parameters**

#### **Dimensional tolerances:**

Length: -1.0 to 2.0mm
Width: -1.0 to 2.0mm
Height: +/- 3.00mm

Flexural Strength:	5.0 MPa (min)
Freeze thaw:	A maximum of $225g/m^2$ loss of mass after 28 cycles of freezing and thawing or A maximum of $500g/m^2$ loss of mass after 49 cycles of freezing and thawing

# Notes:

1. Meets and exceeds the requirements of the CSA A231.2:19 Precast concrete pavers and patio slabs.

2. All data within this document is for reference purpose only and provided as such. Independent engineering should be used for complete site-specific accuracy in all projects.

3. Pedestal set design should be consulted by project specific engineer



Product Name:	Basketweave 24x24
Product Type:	Classic Series Slab

Product Specifications	Length x Width x Height	Length x Width x Height	Length x Width x Height
Dimensions Metric (mm):	600 x 600 x 40		
Dimensions Imperial (inches):	23.62 x 23.62 x 1.57		
Individual Weight Kg:	34.92		
Individual Weight lbs:	77.00		
Pieces per Bundle	25		
Units per Layer			
Bundle Weight Kg	873.0		
Bundle Weight Lbs	1925.0		
Product Texture:			

## Product Uses:

Residential	Commerical				Other		
		Pedestrian	Pedestrian	Vehicular		Slab on	
Pedestrian	Vehicular	only	& Vehicular	Traffic	Accessibility	Pedestal Set	Permeable
X		X				X	

### **Physical Parameters**

### **Dimensional tolerances:**

Length: -1.0 to 2.0mm Width: -1.0 to 2.0mm Height: +/- 3.00mm

Flexural Strength:	5.0 MPa (min)
Freeze thaw:	A maximum of 225g/m <sup>2</sup> loss of mass after 28 cycles of freezing and thawing or A maximum of 500g/m <sup>2</sup> loss of mass after 49 cycles of freezing and thawing

#### Notes:

1. Meets and exceeds the requirements of the CSA A231.2:19 Precast concrete pavers and patio slabs.

2. All data within this document is for reference purpose only and provided as such. Independent engineering should be used for

3. Pedestal set design should be consulted by project specific engineer



Product Name:	Basketweave 12x24
Product Type:	Classic Series Slab

Product Specifications	Length x Width x Height	Length x Width x Height	Length x Width x Height
Dimensions Metric (mm):	300 x 600 x 40		
Dimensions Imperial (inches):	11.81 x 23.62 x 1.57		
Individual Weight Kg:	17.43		
Individual Weight lbs:	38.52		
Pieces per Bundle	25		
Units per Layer			
Bundle Weight Kg	435.8		
Bundle Weight Lbs	963.0		
Product Texture:			

#### Product Uses:

Residential	Commerical				Other		
		Pedestrian	Pedestrian	Vehicular		Slab on	
Pedestrian	Vehicular	only	& Vehicular	Traffic	Accessibility	Pedestal Set	Permeable
X		X				X	

### **Physical Parameters**

#### **Dimensional tolerances:**

Length: -1.0 to 2.0mm Width: -1.0 to 2.0mm Height: +/- 3.00mm

Flexural Strength:	5.0 MPa (min)
Freeze thaw:	A maximum of $225g/m^2$ loss of mass after 28 cycles of freezing and thawing or A maximum of $500g/m^2$ loss of mass after 49 cycles of freezing and thawing

# Notes:

1. Meets and exceeds the requirements of the CSA A231.2:19 Precast concrete pavers and patio slabs.

2. All data within this document is for reference purpose only and provided as such. Independent engineering should be used for complete site-specific accuracy in all projects.

3. Pedestal set design should be consulted by project specific engineer



Product Name:	Basketweave 24x24x50 - Special Order
Product Type:	Classic Series Slab

Product Specifications	Length x Width x Height	Length x Width x Height	Length x Width x Height	
Dimensions Metric (mm):	600 x 600 x 50			
Dimensions Imperial (inches):	23.62 x 23.62 x 2			
Individual Weight Kg:	42.05			
Individual Weight lbs:	92.67			
Pieces per Bundle	21			
Units per Layer				
Bundle Weight Kg	883.0			
Bundle Weight Lbs	1946.0			
Product Texture:	Non-slip, intersecting grid pattern. Slight chamfered edge.			

## Product Uses:

Residential	Commerical				Other		
		Pedestrian	Pedestrian	Vehicular		Slab on	
Pedestrian	Vehicular	only	& Vehicular	Traffic	Accessibility	Pedestal Set	Permeable
$\square$		X				X	

## **Physical Parameters**

#### **Dimensional tolerances:**

Length: -1.0 to 2.0mm Width: -1.0 to 2.0mm Height: +/- 3.00mm

Flexural Strength:	5.0 MPa (min)
Freeze thaw:	A maximum of $225g/m^2$ loss of mass after 28 cycles of freezing and thawing or A maximum of $500g/m^2$ loss of mass after 49 cycles of freezing and thawing

### Notes:

1. Meets and exceeds the requirements of the CSA A231.2:19 Precast concrete pavers and patio slabs.

2. All data within this document is for reference purpose only and provided as such. Independent engineering should be used for complete site-specific accuracy in all projects.

3. Pedestal set design should be consulted by project specific engineer



Product Name:	Basketweave 24x24x65 - Special Order
Product Type:	Classic Series Slab

Product Specifications	Length x Width x Height	Length x Width x Height	Length x Width x Height
Dimensions Metric (mm):	600 x 600 x 65		
Dimensions Imperial (inches):	23.62 x 23.62 x 2.5		
Individual Weight Kg:	55.07		
Individual Weight lbs:	121.33		
Pieces per Bundle	15		
Units per Layer			
Bundle Weight Kg	826.0		
Bundle Weight Lbs	1820.0		
Product Texture:			

### Product Uses:

Residential	Commerical				Other		
		Pedestrian	Pedestrian	Vehicular		Slab on	
Pedestrian	Vehicular	only	& Vehicular	Traffic	Accessibility	Pedestal Set	Permeable
X		X				X	

# **Physical Parameters**

# **Dimensional tolerances:**

Length: -1.0 to 2.0mm Width: -1.0 to 2.0mm Height: +/- 3.00mm

Flexural Strength:	5.0 MPa (min)
Freeze thaw:	A maximum of $225g/m^2$ loss of mass after 28 cycles of freezing and thawing or A maximum of $500g/m^2$ loss of mass after 49 cycles of freezing and thawing

# Notes:

1. Meets and exceeds the requirements of the CSA A231.2:19 Precast concrete pavers and patio slabs.

2. All data within this document is for reference purpose only and provided as such. Independent engineering should be used for complete site-specific accuracy in all projects.

3. Pedestal set design should be consulted by project specific engineer