



# SAFETY DATA SHEET

Issue Date 20-Dec-2015

Revision Date 29-Dec-2016

Version 1

## 1. IDENTIFICATION

### Product identifier

**Product Name** BAKOR 930-18 POLY-TAC RUBBERIZED ADHESIVE

### Other means of identification

**Product Code** BK018  
**UN/ID no** UN1133  
**Synonyms** None

### Recommended use of the chemical and restrictions on use

**Recommended Use** Adhesives and/or sealants  
**Uses advised against** No information available

### Details of the supplier of the safety data sheet

#### **Manufacturer Address**

HENRY COMPANY  
999 N. Sepulveda Blvd., Suite 800  
El Segundo, CA 90245-2716  
Web Site: [www.henry.com](http://www.henry.com) [www.ca.henry.com](http://www.ca.henry.com)

### Emergency telephone number

**Company Phone Number** 800-486-1278  
**Emergency Telephone** CHEMTREC: 800-424-9300  
CHEMTREC: 703-527-3887  
CANUTEC: 613-966-6666

## 2. HAZARDS IDENTIFICATION

### Classification

#### **OSHA Regulatory Status**

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2A
Reproductive toxicity	Category 2
Specific target organ toxicity (single exposure)	Category 3
Specific target organ toxicity (repeated exposure)	Category 2
Flammable liquids	Category 2

### Label elements

#### **Emergency Overview**

#### **Danger**

#### **Hazard statements**

Causes skin irritation  
Causes serious eye irritation  
Suspected of damaging fertility or the unborn child  
May cause respiratory irritation. May cause drowsiness or dizziness  
May cause damage to organs through prolonged or repeated exposure  
Highly flammable liquid and vapor



**Appearance** viscous

**Physical state** liquid

**Odor** Aromatic Petroleum distillates

**Precautionary Statements - Prevention**

Obtain special instructions before use  
Do not handle until all safety precautions have been read and understood  
Use personal protective equipment as required  
Wash face, hands and any exposed skin thoroughly after handling  
Use only outdoors or in a well-ventilated area  
Do not breathe dust/fume/gas/mist/vapors/spray  
Keep away from heat/sparks/open flames/hot surfaces. - No smoking  
Keep container tightly closed  
Ground/bond container and receiving equipment  
Use explosion-proof electrical/ ventilating/ lighting/ equipment  
Use only non-sparking tools  
Take precautionary measures against static discharge  
Keep cool

**Precautionary Statements - Response**

IF exposed or concerned: Get medical advice/attention  
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
If eye irritation persists: Get medical advice/attention  
If skin irritation occurs: Get medical advice/attention  
IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower  
Wash contaminated clothing before reuse  
IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing  
In case of fire: Use CO2, dry chemical, or foam for extinction

**Precautionary Statements - Storage**

Store locked up  
Store in a well-ventilated place. Keep container tightly closed

**Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

**Hazards not otherwise classified (HNOC)**

Not applicable

**Other Information**

May be harmful if swallowed. Toxic to aquatic life with long lasting effects. Toxic to aquatic life.

**Unknown acute toxicity**

24.7821301% of the mixture consists of ingredient(s) of unknown toxicity

**3. COMPOSITION/INFORMATION ON INGREDIENTS**

**Substance**

Not applicable

**Mixture**

Chemical Name	CAS No	Weight-%
---------------	--------	----------

Toluene *	108-88-3	60 - 100
Synthetic Polymer Blend *	Proprietary	10 - 30
Polymer Blend *	Proprietary	3 - 7

\*The exact percentage (concentration) of composition has been withheld as a trade secret.

#### **4. FIRST AID MEASURES**

**Description of first aid measures**

- General advice** In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible). If symptoms persist, call a physician.
- Eye contact** Keep eye wide open while rinsing. Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. If symptoms persist, call a physician.
- Skin contact** Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If symptoms persist, call a physician. Wash contaminated clothing before reuse.
- Inhalation** Remove to fresh air. If breathing is irregular or stopped, administer artificial respiration. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. If symptoms persist, call a physician.
- Ingestion** Call a physician or poison control center immediately. Do not induce vomiting without medical advice. Rinse mouth. Never give anything by mouth to an unconscious person.
- Self-protection of the first aider** Remove all sources of ignition. Use personal protective equipment as required.

**Most important symptoms and effects, both acute and delayed**

**Symptoms** May cause redness and tearing of the eyes. May cause skin irritation. Coughing and/ or wheezing. Drowsiness. Dizziness.

**Indication of any immediate medical attention and special treatment needed**

**Note to physicians** Treat symptomatically.

#### **5. FIRE-FIGHTING MEASURES**

**Suitable extinguishing media**

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Dry chemical, CO<sub>2</sub>, water spray or regular foam.

**Unsuitable extinguishing media** Do not use a solid water stream as it may scatter and spread fire.

**Specific hazards arising from the chemical**

Vapors may travel to source of ignition and flash back. Most vapors are heavier than air. They will spread along ground and collect in low or confined areas (sewers, basements, tanks). Thermal decomposition can lead to release of irritating and toxic gases and vapors.

**Explosion data**

**Sensitivity to Mechanical Impact** None.

**Sensitivity to Static Discharge** May be ignited by heat, sparks or flames.

**Protective equipment and precautions for firefighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

#### **6. ACCIDENTAL RELEASE MEASURES**

**Personal precautions, protective equipment and emergency procedures**

**Personal precautions** ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). All equipment used when handling the product must be grounded. Do not touch or walk through spilled material. Stop leak if you can do it without risk.

**Other Information** Water spray may reduce vapor; but may not prevent ignition in closed spaces.

**For emergency responders** Be aware that gases can spread at ground level (heavier than air) and pay attention to the wind direction. Pay attention to flashback. Remove all sources of ignition. Use personal protective equipment as required.

**Environmental precautions**

**Environmental precautions** Prevent entry into waterways, sewers, basements or confined areas.

**Methods and material for containment and cleaning up**

**Methods for containment** A vapor suppressing foam may be used to reduce vapors. Absorb or cover with dry earth, sand or other non-combustible material and transfer to containers.

**Methods for cleaning up** Use clean non-sparking tools to collect absorbed material. Dike far ahead of liquid spill for later disposal.

**7. HANDLING AND STORAGE**

**Precautions for safe handling**

**Advice on safe handling** Ensure adequate ventilation, especially in confined areas. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Take precautionary measures against static discharges. Use spark-proof tools and explosion-proof equipment. All equipment used when handling the product must be grounded. Use with local exhaust ventilation. Use personal protective equipment as required. Do not breathe dust/fume/gas/mist/vapors/spray.

**Conditions for safe storage, including any incompatibilities**

**Storage Conditions** Keep tightly closed in a dry and cool place. Keep in properly labeled containers. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep containers tightly closed in a cool, well-ventilated place.

**Incompatible materials** Strong oxidizing agents. Strong acids. Strong bases.

**8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

**Control parameters**

**Exposure Guidelines**

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Toluene 108-88-3	TWA: 20 ppm	TWA: 200 ppm Ceiling: 300 ppm	IDLH: 500 ppm TWA: 100 ppm TWA: 375 mg/m <sup>3</sup> STEL: 150 ppm STEL: 560 mg/m <sup>3</sup>

NIOSH IDLH *Immediately Dangerous to Life or Health*

**Appropriate engineering controls**

**Engineering Controls** Showers  
Eyewash stations  
Ventilation systems.

**Individual protection measures, such as personal protective equipment**

<b>Eye/face protection</b>	Wear safety glasses with side shields (or goggles).
<b>Skin and body protection</b>	Wear protective gloves and protective clothing.
<b>Respiratory protection</b>	If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.
<b>General Hygiene Considerations</b>	When using do not eat, drink or smoke. Regular cleaning of equipment, work area and clothing is recommended.

**9. PHYSICAL AND CHEMICAL PROPERTIES**

**Information on basic physical and chemical properties**

<b>Physical state</b>	liquid	<b>Odor</b>	Aromatic Petroleum distillates
<b>Appearance</b>	viscous	<b>Odor threshold</b>	No information available
<b>Color</b>	blue	<b>Remarks • Method</b>	
<b>Property</b>	<b>Values</b>		
<b>pH</b>	No information available		
<b>Melting point / freezing point</b>	No information available		
<b>Boiling point / boiling range</b>	111 °C / 232 °F		
<b>Flash point</b>	6 °C / 43 °F		Pensky-Martens Closed Cup (PMCC)
<b>Evaporation rate</b>	No information available		
<b>Flammability (solid, gas)</b>	No information available		
<b>Flammability Limit in Air</b>			
<b>Upper flammability limit:</b>	7.4%		
<b>Lower flammability limit:</b>	1.4%		
<b>Vapor pressure</b>	3.8 kPa	@ 20 °C	
<b>Vapor density</b>	3.1	.? (Air = 1)	
<b>Relative density</b>	0.9 - 1.3		
<b>Water solubility</b>	Insoluble in water		
<b>Solubility in other solvents</b>	No information available		
<b>Partition coefficient</b>	No information available		
<b>Autoignition temperature</b>	223 °C / 433 °F		
<b>Decomposition temperature</b>	No information available		
<b>Kinematic viscosity</b>	> 100 mm <sup>2</sup> /s	@ 40 °C	
<b>Dynamic viscosity</b>	No information available		
<b>Explosive properties</b>	Not an explosive		
<b>Oxidizing properties</b>	Not applicable		

**Other Information**

<b>Softening point</b>	No information available
<b>Molecular weight</b>	No information available
<b>VOC Content (%)</b>	No information available
<b>Density</b>	No information available
<b>Bulk density</b>	No information available

**10. STABILITY AND REACTIVITY**

**Reactivity**  
No data available

**Chemical stability**  
Stable under recommended storage conditions.

**Possibility of Hazardous Reactions**

None under normal processing.

**Conditions to avoid**

Heat, flames and sparks.

**Incompatible materials**

Strong oxidizing agents. Strong acids. Strong bases.

**Hazardous Decomposition Products**

Thermal decomposition can lead to release of irritating and toxic gases and vapors. Carbon dioxide (CO<sub>2</sub>). Carbon monoxide.

**11. TOXICOLOGICAL INFORMATION**

**Information on likely routes of exposure**

**Product Information**

<b>Inhalation</b>	May cause irritation of respiratory tract. May cause drowsiness or dizziness.
<b>Eye contact</b>	Irritating to eyes.
<b>Skin contact</b>	Irritating to skin.
<b>Ingestion</b>	Based on available data, the classification criteria are not met.

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Toluene 108-88-3	= 2600 mg/kg ( Rat )	= 12000 mg/kg ( Rabbit )	= 12.5 mg/L ( Rat ) 4 h

**Information on toxicological effects**

**Symptoms** Vapors may cause drowsiness and dizziness. Coughing and/ or wheezing. May cause redness and tearing of the eyes. May cause skin irritation.

**Delayed and immediate effects as well as chronic effects from short and long-term exposure**

**Sensitization** Based on available data, the classification criteria are not met.  
**Germ cell mutagenicity** Based on available data, the classification criteria are not met.  
**Carcinogenicity** The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
Toluene 108-88-3	-	Group 3	-	-
Polymer Blend	-	Group 3	-	-

*IARC (International Agency for Research on Cancer)  
Not classifiable as a human carcinogen*

**Reproductive toxicity** Contains a known or suspected reproductive toxin.  
**STOT - single exposure** Target Organs. Respiratory system.  
**STOT - repeated exposure** May cause disorder and damage to the. Central nervous system.  
**Chronic toxicity** Avoid repeated exposure. May cause adverse liver effects.  
**Target Organ Effects** Respiratory system, Eyes, Skin, Central nervous system, kidney, liver.  
**Neurological effects** Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal.  
**Aspiration hazard** Based on available data, the classification criteria are not met.

**Numerical measures of toxicity - Product Information**

The following values are calculated based on chapter 3.1 of the GHS document .

<b>ATEmix (oral)</b>	2,615.00 mg/kg
<b>ATEmix (dermal)</b>	12,070.00 mg/kg
<b>ATEmix (inhalation-dust/mist)</b>	12.57 mg/l

**12. ECOLOGICAL INFORMATION**

**Ecotoxicity**

Harmful to aquatic life with long lasting effects

24.89106 % of the mixture consists of component(s) of unknown hazards to the aquatic environment

**Persistence and degradability**

Not readily biodegradable.

**Bioaccumulation**

Chemical Name	Partition coefficient
Toluene 108-88-3	2.65

**Other adverse effects**

No information available

**13. DISPOSAL CONSIDERATIONS**

**Waste treatment methods**

**Disposal of wastes**

This material, as supplied, is a hazardous waste according to federal regulations (40 CFR 261). Dispose of in accordance with federal, state and local regulations.

**Contaminated packaging**

Disposal should be in accordance with applicable regional, national and local laws and regulations. Do not reuse container.

**US EPA Waste Number**

D001

Chemical Name	RCRA - Halogenated Organic Compounds	RCRA - P Series Wastes	RCRA - F Series Wastes	RCRA - K Series Wastes
Toluene 108-88-3	-	-	Toxic waste waste number F025 Waste description: Condensed light ends, spent filters and filter aids, and spent desiccant wastes from the production of certain chlorinated aliphatic hydrocarbons, by free radical catalyzed processes. These chlorinated aliphatic hydrocarbons are those having carbon chain lengths ranging from one to and including five, with varying amounts and positions of chlorine substitution.	-

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste Status
Toluene 108-88-3	Toxic Ignitable

**14. TRANSPORT INFORMATION**

**DOT**

**UN/ID no** UN1133  
**Proper shipping name** Adhesives  
**Hazard Class** 3

**Packing Group** II  
**Special Provisions** 149, B52, IB2, T4, TP1, TP8  
**Description** UN1133, Adhesives, 3, II  
**Emergency Response Guide Number** 128

**TDG**

**UN/ID no** UN1133  
**Proper shipping name** Adhesives  
**Hazard Class** 3  
**Packing Group** II  
**Description** UN1133, Adhesives, 3, II

**IATA**

**UN/ID no** UN1133  
**Proper shipping name** Adhesives  
**Hazard Class** 3  
**Packing Group** II  
**ERG Code** 3L  
**Special Provisions** A3  
**Description** UN1133, Adhesives, 3, II

**IMDG**

**UN/ID no** UN1133  
**Proper shipping name** Adhesives  
**Hazard Class** 3  
**Packing Group** II  
**EmS-No** F-E, S-D  
**Description** UN1133, Adhesives, 3, II, (6°C c.c.)

**15. REGULATORY INFORMATION**

All components used in this product are on the TSCA Inventory and the Canadian DSL.

**International Inventories**

**TSCA** Complies  
**DSL/NDL** Complies  
**EINECS/ELINCS** Complies  
**IECSC** Complies  
**KECL** Complies  
**PICCS** Complies  
**AICS** Complies

**Legend:**

**TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory  
**DSL/NDL** - Canadian Domestic Substances List/Non-Domestic Substances List  
**EINECS/ELINCS** - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances  
**ENCS** - Japan Existing and New Chemical Substances  
**IECSC** - China Inventory of Existing Chemical Substances  
**KECL** - Korean Existing and Evaluated Chemical Substances  
**PICCS** - Philippines Inventory of Chemicals and Chemical Substances  
**AICS** - Australian Inventory of Chemical Substances

**US Federal Regulations**

**SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	SARA 313 - Threshold Values %
Toluene - 108-88-3	1.0

**SARA 311/312 Hazard Categories**



<b>Acute health hazard</b>	Yes
<b>Chronic Health Hazard</b>	Yes
<b>Fire hazard</b>	Yes
<b>Sudden release of pressure hazard</b>	No
<b>Reactive Hazard</b>	No

**CWA (Clean Water Act)**

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Toluene 108-88-3	1000 lb	X	X	X

**CERCLA**

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Toluene 108-88-3	1000 lb 1 lb	-	RQ 1000 lb final RQ RQ 454 kg final RQ RQ 1 lb final RQ RQ 0.454 kg final RQ

**US State Regulations**

**California Proposition 65**

This product contains the following Proposition 65 chemicals

Chemical Name	California Proposition 65
Toluene - 108-88-3	Developmental

**U.S. State Right-to-Know Regulations**

Chemical Name	New Jersey	Massachusetts	Pennsylvania
Toluene 108-88-3	X	X	X

**U.S. EPA Label Information**

**EPA Pesticide Registration Number** Not applicable

**16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION**

<b>NFPA</b>	<b>Health hazards</b> 2	<b>Flammability</b> 3	<b>Instability</b> 0	<b>Physical and Chemical Properties</b> -
<b>HMIS</b>	<b>Health hazards</b> 2*	<b>Flammability</b> 3	<b>Physical hazards</b> 0	<b>Personal protection</b> X
<i>Chronic Hazard Star Legend</i>	<i>* = Chronic Health Hazard</i>			

**Issue Date** 20-Dec-2015

**Revision Date** 29-Dec-2016

**Revision Note**  
No information available

**Disclaimer**

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet**