



SAFETY DATA SHEET

FiberTite® FTR-290 Adhesive

Rev. Date: 17 Oct 2014

SECTION 1. PRODUCT & COMPANY INFORMATION

Product Name: FTR-290 Roofing Adhesive

Recommended Use: Roofing adhesive

Manufacturer: SEAMAN CORPORATION
1000 Venture Blvd.
Wooster, OH 44691 USA

PHONE: (330) 262-1111
INTERNET: www.seamancorp.com
24-HR EMERGENCY: (800) 424-9300 (Chemtrec)

SECTION 2. HAZARDS IDENTIFICATION

Pictograms:



Signal Word: DANGER

GHS Classification:

Flammable Liquid – Category 2
Eye Irritant – Category 2A
Skin Irritant – Category 2
Reproductive Toxicant – Category 2
Aspiration Hazard – Category 1
Specific Target Organ Toxicity (Single Exposure) – Category 3
Specific Target Organ Toxicity (Repeated Exposure) – Category 2

Hazard Statements:

Highly flammable liquid and vapor
May be fatal if swallowed and enters airways
Causes skin irritation
Causes serious eye irritation
Suspected of damaging fertility or the unborn
May cause drowsiness or dizziness
May cause damage to organs (central nervous system, kidneys, liver) through prolonged or repeated exposure

Precautionary Statements:

Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Keep away from heat.
Keep container tightly closed.
Ground/bond container and receiving equipment.
Use explosion-proof electrical/ventilating/lighting equipment.

Use only non-sparking tools.
Take precautionary measures against static discharge.
Do not breathe vapor.
Wash face, hands and any exposed skin thoroughly after handling.
Use only outdoors or in a well-ventilated area.
Wear protective gloves/protective clothing/eye protection/face protection.
Use personal protective equipment as required.

Response:

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting.
IF ON SKIN: Wash with plenty of soap and water.
IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.
Continue rinsing.
IF exposed or concerned: Get medical advice/attention.
Call a POISON CENTER or doctor/physician if you feel unwell.
If skin irritation occurs: Get medical advice/attention.
If eye irritation persists: Get medical advice/attention.
Take off contaminated clothing and wash before reuse.
IN CASE OF FIRE: Use foam/CO2/powder/water spray for extinction..

Storage:

Store in a well-ventilated place. Keep container tightly closed.
Keep cool.
Store locked up.

Disposal:

Dispose of contents/container in accordance with local/regional/national regulations

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

<u>Components</u>	<u>CAS No.</u>	<u>% by weight</u>
Acetone	67-64-1	35-60
Nitrile Rubber/polymeric blend	n/a	25-40
Toluene	108-88-3	10-30

SECTION 4. FIRST AID MEASURES

Inhalation: Move to fresh air. Seek medical attention if symptoms persist.
Skin Contact: Wash exposed skin with soap and water. Do not use solvents or thinners. If irritation develops or persists, seek medical attention.
Eye Contact: Flush eyes with plenty of water for at least 15 minutes. Seek medical attention.
Ingestion: Seek medical attention. Do not induce vomiting.

SECTION 5. FIRE FIGHTING MEASURES

Flammable Properties: Material is highly flammable. Likely to catch fire from nearby spark. Static charge may accumulate.

Suitable Extinguishing Media: alcohol resistant foam, CO2, powders, water spray

Products of Combustion: Fire will produce dense black smoke. Carbon monoxide and carbon dioxide may be produced from decomposition.

Protection of Firefighters: Firefighters should wear self-contained breathing apparatus and full fire-fighting turnout gear. No special procedures are expected to be necessary for this product.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal Precautions: Use personal protection recommended in Section 8.
Environmental Precautions: No special procedures necessary
Methods for Containment: No special procedures necessary
Methods for Clean-up: No special procedures necessary

SECTION 7. HANDLING AND STORAGE

Handling: Use protective equipment recommended in Section 8. Use only in well ventilated area. Eliminate any source of ignition. Ground and bond all equipment when handling. Any electrical equipment used around vapors should meet the applicable requirements of the local electrical code. Wash hands after contact.

Storage: Storage temperature 60°F to 95°F (15°C to 35°C). Shelf life one year from manufacture date. Keep away from oxidizing agents and strongly acid or strongly alkaline materials. Avoid heating or direct sunlight. Material will evaporate quickly.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

EXPOSURE GUIDELINES

COMPONENT	OSHA (PEL)	ACGIH (TLV)	NIOSH (REL)	COMMENTS
Acetone (67-64-1)	1000 ppm (2400 mg/m ³) TWA	500 ppm (1187 mg/m ³) TWA; 750 ppm (1780 mg/m ³) STEL	-	
Toluene (108-88-3)	200 ppm (590 mg/m ³) TWA; 300 ppm STEL	20 ppm TWA	-	

PERSONAL PROTECTIVE EQUIPMENT

Engineering Controls: Provide local exhaust ventilation
Eye/Face: Wear safety glasses
Skin: Wear chemical resistant protective gloves
Respiratory: If exposure limits are exceeded, NIOSH approved respiratory protection must be provided
General Hygiene: Wash hands with soap and water after handling material.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Clear	Odor: Solvent
Odor threshold: Not available	pH: Not available
Melting/Freezing Point: -95°C	Boiling Point: 56°C (133°F)
Flash Point: -17°C (1.4°F)	Evaporation Rate: >1.0 (butyl acetate=1)
Flammability: Category 2	LFL/UFL: 1.2% / 12.8%
Vapor Pressure: 190 mmHg @ 20°C	Vapor Density: Greater than air
Relative Density: 0.896	Solubility: Solvent soluble in water
Partition Coefficient K_{ow}: Not available	Auto-Ignition Temp.: 465-536°C (869-997°F)
Decomposition Temp.: Not applicable	Viscosity: Not available

VOC Content: 234.1 g/L (EPA Method 24)
 Photochemically reactive VOC: 127.7 g/L

SECTION 10. STABILITY AND REACTIVITY

Chemical Stability:	Stable at recommended storage and handling conditions
Conditions to Avoid:	Sources of ignition
Incompatible Materials:	Oxidizing agents, strong acids, strong bases
Hazardous Decomposition:	Carbon monoxide, carbon dioxide
Hazardous Reactions:	Will not occur

SECTION 11. TOXICOLOGY INFORMATION

POTENTIAL HEALTH EFFECTS:

Summary:	Material is flammable, irritating to eyes and skin, can cause dizziness/drowsiness
Inhalation:	May cause dizziness and/or drowsiness, headaches, and irritation of the lungs
Skin Contact:	Drying of skin and dermatitis may occur
Eye Contact:	May cause irritation, redness, and burning; vapors may also cause irritation
Ingestion:	Irritation of gastrointestinal tract, large quantities may have toxic effects
Target Organs:	Central nervous system, skin, eyes, liver, kidneys

ACUTE TOXICITY

General Information: In high concentration the material is irritating to the mucous membranes, can induce a narcotic effect, and cause loss of coordination and reaction.

Component Analysis:

Acetone (67-64-1):
Oral LD50 Rat: >5000 mg/kg
Dermal LD50 Rabbit: >15700 mg/kg
Inhalation (rat): 32000 mg/m ³ (4-hr dose)
Toluene (108-88-3):
Oral LD50 Rat: 636 mg/kg
Dermal LD50 Rabbit: 14100 mg/kg
Inhalation (mouse): 440 mg/L (24-hr dose)

CARCINOGENICITY

General Information: This product is not classified as a carcinogen or potential carcinogen by OSHA, NTP, ACGIH, or IARC. No specific data available.

Component Analysis:

Toluene (108-88-3):
IARC: 3 – Unclassifiable as to Carcinogenicity in Humans
ACGIH: A4 – Not classifiable as a Human Carcinogen

CHRONIC TOXICITY

No data is available on mutagenicity, reproductive effects, or developmental effects.

SECTION 12. ECOLOGICAL INFORMATION

This product contains components that will normally float on water. These components may be harmful to aquatic organisms and may cause long term effects in the aquatic environment.

Do not empty into drains or waterways.

SECTION 13. DISPOSAL CONSIDERATIONS

Dispose of waste in accordance with Federal, State, and local environmental control regulations. This material may be classified as hazardous under the Resource Conservation and Recovery Act. (40 CFR 261)

SECTION 14. TRANSPORTATION INFORMATION

This product is hazardous for transportation.

Shipping Name: Adhesives (contains toluene, acetone)
Class: 3 Packing Group: II ID No.: NA1133 NAERG: 128

SECTION 15. REGULATORY INFORMATION

SARA Title III: Health: Acute YES Chronic YES EHS NO
Physical: Fire YES Reactivity NO Pressure NO

SARA 313 (TRI): This product contains the following chemicals subject to reporting under Superfund Amendments Reauthorization Act, Title III, Section 313 (Toxic Release Inventory):

<u>Component</u>	<u>% by weight</u>
Toluene (CAS# 108-88-3)	1-5 %

California Proposition 65: **WARNING:** This material contains a chemical known to the State of California to cause birth defects or other reproductive harm: Toluene (CAS# 108-88-3)

SECTION 16. OTHER INFORMATION

The data in this Safety Data Sheet relates only to the specific material designated herein and does not relate to use in combination with any other material or in any process. No warranty of merchantability or any other warranty, expressed or implied, is given. In no case shall the information provided herein be considered a part of the terms and conditions of sale. Seaman Corporation assumes no obligation or liability for the information given or results obtained. All materials may present unknown hazards and should be used with caution. Final determination of suitability of any material is the sole responsibility of the user.

For questions related to the safety of this product, e-mail msds@seamancorp.com or call (330) 262-1111.

FiberTite® is a registered trademark of Seaman Corporation.



Innovative Customer Solutions through Fiber and Polymer Technology

1000 VENTURE BLVD. ▪ WOOSTER, OHIO 44691
PHONE: (330) 262-1111 ▪ FAX: (330) 263-6950 ▪ www.seamancorp.com