

DESCRIPTION & USE

LEXCAN HI-PRO PVC T-JOINT COVER is a non-reinforced PVC membrane, with Elvaloy® KEE, formed into a 114 mm (4.5") diameter circle. T-JOINT COVER is used to reinforce "T" intersections in field seams and at various angle seam transitions.

FEATURES & BENEFITS

Prefabricated Membrane Accessory - provides labour savings and a more professional and consistent appearance than field cut T-Joint covers.

TECHNICAL DATA

Typical Properties & Characteristics	
Material:	Non-reinforced PVC with Elvaloy®* KEE
Size:	114 mm (4.5") diameter
Available Colours:	White and Grey

* Elvaloy® KEE is a registered trademark of Dow.

PACKAGING

Quantity per Box:	100 per box
Box Weight:	2.9 kg (6.4 lbs)

STORAGE

Store indoors, out of direct sunlight, and keep clean and dry prior to application.

INSTALLATION

Note: Prior to installation, ensure the welding surface is clean by using LEXCAN SINGLE PLY MEMBRANE CLEANER.

1. Center the T-JOINT COVER over the splice intersection. Begin welding at the center point and work towards the outside. Use the edge of the roller to crease the T-JOINT COVER into the underlying seams, to achieve a proper seal.
2. Once the T-JOINT COVER has completely cooled, using a seam probe, check all splices for voids and cold welds. Make any needed repairs.

